

A MODEM INTEGRATED INTO A RADIO RECEIVER UTILIZING A COMMUNICATION PORT

Technical Field

5 The present invention relates to a radio system and more particularly to a radio system incorporating a modem for sending and receiving electronic messages to and from a personal digital assistant.

Background of the Invention

10 The accessibility of information poses unique problems in a highly mobile society. Cellular technology provides access to phone lines in a mobile environment. However, it is often necessary to send and receive electronic messages while in an area that does not have access to a computer terminal and a modem, such as a moving vehicle.

15 Personal Digital Assistants (PDA's) can be used to display electronic messages. Unfortunately, many PDA's are only capable of displaying messages that have been downloaded to the PDA from a computer. So while these items help to display messages, they are not capable of sending or receiving information without access to a computer terminal.

20 Currently, there is a need for access to electronic mail, or other Internet information, through a cellular link in a vehicle that conveniently allows a driver to send and receive electronic messages while in the vehicle.

Summary of the Invention

25 The present invention is a system and a method for sending and receiving electronic messages through a radio. The present invention is an integrated audio and communications system having a radio that incorporates a modem for sending and receiving electronic messages through a personal digital assistant and a cellular phone. The radio system includes a modem that is accessed by the personal digital assistant and the cellular phone by way of a communications port. The modem is enhanced for cellular performance.

09637254-072000

The communications port provides a cellular link to an Internet service provider for two-way electronic message transfers through the personal digital assistant. The radio monitors signals sent from the communications port and the personal digital assistant and displays messages indicating the status of the communication connection.

It is an object of the present invention to provide a method for sending and receiving electronic messages using an automobile's radio. It is another object of the present invention to provide a link between a cellular phone and a personal digital assistant using the radio. Yet another object of the present invention is to modify the vehicle's radio with a cellular modem for connecting a personal digital assistant to an Internet service provider.

Other objects and features of the present invention will become apparent when viewed in light of the detailed description of the preferred embodiments and when taken in conjunction with the attached drawings and appended claims.

Brief Description of the Drawings

In order that the present invention may be well understood, there will now be described some embodiments thereof, given by way of example, with reference to the accompanying drawings, in which:

FIGURE 1 is a block diagram of a radio system and communications port according to the present invention; and

FIGURE 2 is a flow chart of the method of the present invention;

FIGURE 3 is a continuation of the flow chart shown in Figure 2;

FIGURE 4 is a continuation of the flow chart shown in Figure 3; and

FIGURE 5 is a continuation of the flow chart shown in Figure 4.

Figure 1 is a block diagram of the present invention, which is a system 10 by which a radio 14 is used to access electronic messages through a personal digital assistant (PDA) 20. The radio 14 is equipped with a cellular modem 12 and a communication port 16 that provides a link between a cellular phone 18 and the modem 12. The modem 12 and the cellular phone 18 provide the PDA with access to an Internet service provider, thereby allowing a user to send and receive electronic messages through the PDA 20 while the status of the communication connection is displayed by the radio 14.

In the preferred embodiment, the modem is 14.4K baud. The modem 14 has a specific protocol that is enhanced for cellular performance. The communication port 16 provides access to the phone audio 22 in order to facilitate the connection between the phone 18 and the modem 12 in the radio 14. During normal radio operation, the modem 12 is not powered. A slave microprocessor 24 in the radio 14 monitors transmit (Tx), receive (Rx) and data terminal ready (DTR) input signals sent from the PDA 20. The input signals are converted from RS232 to TTL levels by an RS232/TTL converter 26. The converted signals are buffered by a dual Universal Asynchronous Receiver/Transmitter, or DUART 28.

20 The transmit signal (Tx) from the PDA 20 is used to supply information for a phone number to be dialed and to terminate a call. The receive signal (Rx) is used to provide the modem 12 status. The DTR signal contains information about the status of the call. During modem 12 use, the communication port 16 will disable all other functions on the radio 14 except
25 for volume control and an end function. The modem 12 should be configured so as not to answer incoming calls.

The radio system 10 of the present invention has a communications protocol that allows the radio 14 to transmit information such as a request for phone status, a request to load a phone number to the phone and a request to end a phone call. The radio 14 must be capable of decoding and acting on standard AT commands used by the modem. In the present

The PDA 20 is used to send and receive electronic mail messages by way of the communications port 16 through an Internet connection that is established through the cellular phone 18. The messages are sent and received as ASCII text. Therefore, the PDA 20 must have a text program. It should be noted that a traditional electronic mail program might be used in conjunction with customized software to convert the message files to text. There are no limitations on the text program that can be used in conjunction with the present invention.

Figure 3 is a continuation of the flow chart shown in Figure 2 and shows the method of the present invention when the modem is connected and the phone is available 200. The radio and the communications port begin 30 202 the modem session. The communications port disables 204 all of the

5

10

15

30

call was not completed. For example, the message may read, "UNABLE TO COMPLETE CALL". Then, the radio terminates 318 the call and returns 500 to the point in the system where the radio waits 111 to verify the availability of the phone.

5 Once the method determines that a computer connection has been established 304 the flow chart continues 400 as shown in Figure 5. Referring now to Figure 5, the radio monitors 402 the modem for the progress of the call and verifies the modem is connected. If the radio determines that the connection is not complete 404, the method will wait 406 until the
10 connection lasts for a predetermined period of time and then either resumes monitoring 402 or terminates 408 the communication session and displays a message indicating the same, returning 500 to the point in Figure 2 where the radio waits 111 for the availability of the phone.

 Referring again to Figure 5, once the method determines that
15 the connection is complete 410, the radio releases the mono channel 412 and displays a message indicating the status of the file transfer to the PDA. For example, the message may read, "BEGINNING FILE TRANSFER". The radio monitors 414 the signal traffic and looks for a loss of the connection or a hang-up signal from the PDA. If the call is not complete, the method of the
20 present invention waits 416 for a predetermined period of time and looks for signal traffic. If there is signal traffic, the method resumes monitoring signal traffic 414. If there is no signal traffic for a predetermined period of time, the radio notifies the communications port that the session has been terminated and releases the mono channel if necessary. The radio may also display a
25 message indicating the status of the communications session. For example, "UNALBE TO COMPLETE CALL".

 When the call is completed 420, the radio displays 422 a message indicating the call is complete, for example, "CALL COMPLETE", and returns 500 to the point, shown in Figure 2, where the radio waits 111 for
30 the availability of the phone.

The system and method of the present invention a radio equipped with a modem and establishes a connection between the PDA and the modem, and a connection between the cellular phone and the modem to allow the PDA to access electronic messages. The microprocessor in the radio is

5 capable of distinguishing different signals to determine the status of the connection and provide updates on the radio's display. For example, the radio is capable of determining if the phone number is being dialed, if the connection is successful, if the data is being transmitted, and if the connection is being terminated. It is also capable of determining if there is a problem in

10 the communication and will display an appropriate message. The system and method of the present invention allow a useful connection to electronic messages through a radio that allows access to information not otherwise readily available to someone traveling as by car or other mode of transportation.

15 While particular embodiments of the invention have been shown and described, numerous variations and alternate embodiments will occur to those skilled in the art. Accordingly, it is intended that the invention be limited only in terms of the appended claims.

090627234 072800